

KLEERSEAL

Technical Information

KleerSeal Water Based Sealer

Product Description:

VMC KleerSeal is an environmentally safe, non-toxic, and silicone free stone impregnator. It will greatly reduce all types of deterioration to stone and porous cementitious materials.

Special Features:

Oil resistant
Water Resistant
Mildew Resistant
Non-Flammable
Non-Toxic
Ultraviolet Stabilized
Prevents Efflorescence
Long Lasting Protection
Silicone-Free
Environmentally Safe

Where and When to Use:

KleerSeal can be used for walls, floors, statues, parking lots and water fountains.

Packaging:

8 oz. (in kit)
1 gallon (3.8L)
32 oz.
30 gallon (113.6L)
55 gallon (208.2L)

Storage:

Storage temperature: 120°F (49°C) maximum

Directions for use:

- 1) Apply using a cloth, brushing, rolling, or flooding.
- 2) For more porous surfaces such as grout, joints, concrete, limestone, and slate a second application may be applied after the first has dried.
- 3) Do not allow to completely dry on polished surfaces. Remove all excess KleerSeal from the polished surface before it dries.

Note:

For floors, work in 5ft. x 5 ft. areas. For countertops, work in 2 ft. x 2 ft. areas. The suggested coverage rate for highly porous material is 150-300 sq. ft. gallon (13.9-278.7 sq. meters/3.8 liters), the rate for less porous material is 500-1000 sq. ft. /gallon. (46.5-92.9 sq. meters/3.8 liters)

Product Specifications:

Physical State: Liquid
Odor: Slight characteristic
Appearance: White to pale yellow
pH: 7-8
Solubility in water: Infinite
Specific gravity: 1.0

Precautions Summary:

Eyes: May cause irritation
Skin: May cause irritation
Inhalation: Mists may be irritating to respiratory tract in high concentrations
Ingestion: Minimal toxicity
Flash point: None

VMC TECHNICAL ASSISTANCE CORPORATION

8311 EASTPOINT DRIVE, SUITE 800

DALLAS, TX 75227

TELEPHONE

(214)381-8456

FAX

(214)381-4896

WEB

www.vmc-tac.com

KLEERSEAL
TECHNICAL INFORMATION

